

# VERITY® 1741 UV-VIS Detector

Specially Designed for Secure Semi-Preparative and Preparative HPLC Applications



SPEC SHEET | PURIFICATION

VERITY® 1741 UV-VIS DETECTOR

With the ability to scan multiple different wavelengths simultaneously, the VERITY® 1741 UV-VIS Detector provides more significant detection information required for a wide array of purification applications.

## EXPLICITLY DESIGNED FOR SEMI-PREPARATIVE AND PREPARATIVE HPLC

The reliable and versatile VERITY 1741 Detector has a large scanning range of 200-800 nm and offers flow cell pathlengths ranging from 0.05 to 1.3 mm with a compatible flow rate of up to 500 ml/min.

## EASY TO USE AT A LOW COST OF OWNERSHIP

The VERITY 1741 Detector features a large display for stand-alone operation and also offers a built-in counter for monitoring lamp life, helping you avoid purification interruptions. The easy-to-replace flow cells and long-life lamp decrease the detector's downtime, saving you money.

## FULLY INTEGRATED WITH TRILUTION® LC SOFTWARE

TRILUTION® LC Software for purification fully controls the VERITY 1741 Detector to monitor up to eight different wavelengths to trigger fraction collection and display real-time spectra. The VERITY 1741 Detector is a powerful addition to our VERITY® preparative HPLC systems that allows safe compound purification.



**Figure 1**  
VERITY® 1741 UV-VIS Detector



**Figure 2**  
VERITY® 271 HPLC System

## VERIFIABLE SCIENTIFIC RESULTS REQUIRE RELIABLE PURIFICATION SYSTEMS

Get the accuracy and precision you need for trusted results with VERITY® purification systems. Whether you isolate large or small molecules or need milligram to kilogram purifications, our VERITY systems offer you a wide array of components to build the perfect system to meet your specific needs. All systems are easily controlled by intuitive software, letting you focus on science. Backed by our long history in chromatography, you are reassured that VERITY solutions are built to last and will make your life in the lab easier.

SPECIFICATION	DEFINITION OR VALUE																																													
Control	Front panel control or computer control via Ethernet and TRILUTION® LC Software																																													
Wavelength Range	200–800 nm (256 CCD elements)																																													
Wavelength Accuracy / Reproducibility	± 1 nm / ± 0.5 nm																																													
Flow Cells	<table border="1"> <thead> <tr> <th>Part Number</th> <th>Pathlength</th> <th>Internal Volume</th> <th>Maximum Flow Rate</th> <th>Connecting Thread Internal Tubing</th> </tr> </thead> <tbody> <tr> <td>14161011</td> <td>1.3 mm</td> <td>55 µL</td> <td>200 mL/min</td> <td>10-32 1/16" stainless steel tubing</td> </tr> <tr> <td>14161014</td> <td>0.5 mm</td> <td>50 µL</td> <td>200 mL/min</td> <td>10-32 1/16" stainless steel tubing</td> </tr> <tr> <td>14161012</td> <td>0.1 mm</td> <td>40 µL</td> <td>200 mL/min</td> <td>10-32 1/16" stainless steel tubing</td> </tr> <tr> <td>14161013</td> <td>0.05 mm</td> <td>40 µL</td> <td>200 mL/min</td> <td>10-32 1/16" stainless steel tubing</td> </tr> <tr> <td>14161015</td> <td>1.3 mm</td> <td>55 µL</td> <td>500 mL/min</td> <td>¼-28 1/8" FEP tubing</td> </tr> <tr> <td>14161018</td> <td>0.5 mm</td> <td>50 µL</td> <td>500 mL/min</td> <td>¼-28 1/8" FEP tubing</td> </tr> <tr> <td>14161016</td> <td>0.1 mm</td> <td>40 µL</td> <td>500 mL/min</td> <td>¼-28 1/8" FEP tubing</td> </tr> <tr> <td>14161017</td> <td>0.05 mm</td> <td>40 µL</td> <td>500 mL/min</td> <td>¼-28 1/8" FEP tubing</td> </tr> </tbody> </table>	Part Number	Pathlength	Internal Volume	Maximum Flow Rate	Connecting Thread Internal Tubing	14161011	1.3 mm	55 µL	200 mL/min	10-32 1/16" stainless steel tubing	14161014	0.5 mm	50 µL	200 mL/min	10-32 1/16" stainless steel tubing	14161012	0.1 mm	40 µL	200 mL/min	10-32 1/16" stainless steel tubing	14161013	0.05 mm	40 µL	200 mL/min	10-32 1/16" stainless steel tubing	14161015	1.3 mm	55 µL	500 mL/min	¼-28 1/8" FEP tubing	14161018	0.5 mm	50 µL	500 mL/min	¼-28 1/8" FEP tubing	14161016	0.1 mm	40 µL	500 mL/min	¼-28 1/8" FEP tubing	14161017	0.05 mm	40 µL	500 mL/min	¼-28 1/8" FEP tubing
	Part Number	Pathlength	Internal Volume	Maximum Flow Rate	Connecting Thread Internal Tubing																																									
	14161011	1.3 mm	55 µL	200 mL/min	10-32 1/16" stainless steel tubing																																									
	14161014	0.5 mm	50 µL	200 mL/min	10-32 1/16" stainless steel tubing																																									
	14161012	0.1 mm	40 µL	200 mL/min	10-32 1/16" stainless steel tubing																																									
	14161013	0.05 mm	40 µL	200 mL/min	10-32 1/16" stainless steel tubing																																									
	14161015	1.3 mm	55 µL	500 mL/min	¼-28 1/8" FEP tubing																																									
	14161018	0.5 mm	50 µL	500 mL/min	¼-28 1/8" FEP tubing																																									
	14161016	0.1 mm	40 µL	500 mL/min	¼-28 1/8" FEP tubing																																									
14161017	0.05 mm	40 µL	500 mL/min	¼-28 1/8" FEP tubing																																										
Maximum pressure for all flow cells is 2 MPa (290 psi, 20 bar)																																														
Liquid Contact Materials	FEP, fused silica, stainless steel, PEEK, KEL-F																																													
Digital Output / Output Signal	1 V/AU / Four wavelength (channels) or scan with speed up to 20 Hz with step of 1 nm																																													
Power Requirements	<b>Voltage:</b> 100–240 V AC <b>Frequency:</b> 50/60 Hz																																													
Environmental Conditions	Indoor use only Altitude: up to 2000m <b>Temperature:</b> 5°C–40°C <b>Humidity:</b> maximum relative humidity 80% for temperatures up to 31°C decreasing linearly to 50% relative humidity at 40°C <b>Voltage fluctuations:</b> up to ± 10% of nominal voltage Overvoltage category I Pollution degree 2																																													
Safety and Compliance	The detector has been certified to safety standards specified for Canada, Europe, and the United States. Refer to the instrument rear panel label and the Declaration of Conformity document for the current standards to which the instrument has been tested																																													
Dimensions (W x H x D)	28.5 cm x 14.9 cm x 50 cm (11.2 x 5.9 x 19.7 in.)																																													
Weight	7.5 kg (16.5 lb.)																																													